



# DOUBLEFIX UNIVERSAL

## EXTREMELY STRONG DOUBLE-SIDED MOUNTING TAPE



### PRODUCT DESCRIPTION

Extremely strong double-sided tape for permanently mounting and affixing objects in indoor and outdoor areas. The heavy-duty mounting tape for a universal use. Provides a permanent and secure hold on almost all smooth and slightly rough surfaces, e.g. metal, tiles, plastic, glass, wood, plaster, stone and concrete. Ideal for mounting signs, house numbers, holders, hooks, shelving elements, cable channels, decorative objects and profiles, and much more. Fully load-bearing after 60 minutes. Moisture-resistant.

### FIELD OF APPLICATION

Ideal for mounting signs, house numbers, holders, hooks, shelving elements, cable channels, decorative objects and profiles, etc. on almost all smooth and slightly rough surfaces, indoors and outdoors. Suitable for metal, tiles, plastic, glass, wood, plaster, stone and concrete.

### PROPERTIES

- Double-sided mounting tape
- Extremely high adhesive power
- Universal use
- For smooth and rough surfaces
- For indoors and outdoors
- Humidity resistant
- Temperature resistant
- Clean, easy, fast

### PREPARATION

**Working Conditions:** The minimum working temperature is 10 °C.

**Surface Requirements:** The surfaces to be glued must be firm, clean, dry, and free of grease and dust.

**Preliminary Surface Treatment:** For best results, first cleanse the surfaces to be glued (e.g. with alcohol or white spirit).

### APPLICATION

#### Directions for use:

Stick the product onto the object to be mounted without creating air pockets. Bonding objects >4 kg requires several strips, distributed vertically with a distance of 3-5 cm. Remove the protective film without touching the adhesive. Affix the object to the desired spot and press hard.

**Stains/residue:** Remove tape residue with white spirit.

**Points of attention:** Do not touch the adhesive as this reduces the tape's adhesive strength.

### TECHNICAL SPECIFICATIONS

Carrier type:	Polyester fabric
Chemical base:	Synthetic rubber
Chemicals resistance:	Limited
Colour:	Transparent (yellowish)
Holding power:	>168h (3kg)
Initial tack:	Extremely high
Minimum temperature resistance:	-10 °C
Maximum temperature resistance:	75 °C
Moisture resistance:	Good
Peel adhesion:	SS 55 N/25mm
Tensile Strength (N/25 mm) approx.:	80 N/25 mm
Thickness (mm):	0.81 mm
UV resistance:	Good

### PACK SIZES

Tape: 1.5m x 19mm on blistercard

### STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.