



SILICONE REMOVER

TO SAFELY AND THOROUGHLY REMOVE OLD SILICONE SEALANT RESIDUES



APPLICATION

Directions for use:

Shake closed bottle vigorously for about a minute. Cut old sealant loose with a sharp box cutter/ knife. Use the hook of the BISON Multitool to pull out the old sealant out of the joint. Apply the paste generously onto the old sealant residue. Allow to act for at least 30 minutes. Remove old sealant residues with cleaning cloth or sponge. If necessary, repeat the treatment. Clean the joint thoroughly with a sponge and water. Degrease the surface with a lint-free cloth and ammonia. Let it dry thoroughly. Ready for a new sealant application.

Advice: Test the remover on a non-visible spot as staining may occur on sensitive materials.

TECHNICAL SPECIFICATIONS

| | |
|------------------|------------------------|
| Density approx.: | 0,84 g/cm ³ |
| Viscosity: | Gel |

STORAGE CONDITIONS

Store in properly sealed packaging in a dry place at between +5 °C and +25 °C.

PRODUCT DESCRIPTION

For thoroughly removing cured silicone sealant residues Simple and safe to use without damage.

FIELD OF APPLICATION

Suitable for thoroughly removing cured silicone sealant residues in joints and on substrates. Can be used on ceramic tiles, glass, metal, synthetics, laminates, aluminium and enamels.

Not suitable for to be used on nylon. May cause staining on porous materials and painted surfaces.

PROPERTIES

- Safe to use without damage
- Easy to apply
- Thorough effect

PREPARATION

Working Conditions: Do not use in temperatures $\leq +5$ °C.

Surface Requirements: The substrate must be properly dry, clean and free of dust and grease. Remove as much of the existing silicon sealant as possible .

Preliminary Surface Treatment: Use a sharp knife/putty knife to cut away the silicone sealant as much as possible and a dry cloth for the last remaining bits.

Tools: BISON Multitool, Sharp box cutter, Cleaning Cloth, Sponge

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.