KLUS TAPE
SUPER-STRONG, HEAVY-DUTY TEXTILE TAPE WITH PE COATING

APPLICATION
Directions for use:
Stick the tape onto the object without touching the adhesive.
Stains/residue: Remove tape residue with white spirit.

TECHNICAL SPECIFICATIONS

Carrier type:	LDPE
Chemical base:	Synthetic rubber
Initial tack:	Extremely high
Minimum temperature resistance:	-15 °C
Maximum temperature resistance:	60 °C
Peel adhesion:	SS 28 N/25mm
Rolling ball tack:	<3 cm
Tensile Strength (N/25 mm) approx.:	105 N/25 mm
Thickness (mm):	0.22 mm
Colour:	Grey

STORAGE CONDITIONS
Store in a cool, dry place out of direct sunlight.

PRODUCT DESCRIPTION
Super-strong, heavy-duty textile tape with PE coating for waterproof repairing, strengthening, sealing, connecting and protecting. Adheres to almost all surfaces, like e.g. stone, concrete, metal, wood and many plastics. Extremely resistant and solid. Suitable for indoor and outdoor use thanks to its UV-stability and resistance to temperatures of between -15 °C and +70 °C. Can be torn off manually and written on.

FIELD OF APPLICATION
For waterproof repairing, strengthening, sealing, connecting and protecting, indoors and outdoors. Adheres to metal, stone, concrete, wood and plastics. Super-strong duct tape for a universal use.

PROPERTIES
· Super strong
· Extra initial high tack
· Universal
· Indoor and Outdoor
· Temperature resistant
· Waterproof
· UV resistant
· Can be torn off manually

PREPARATION
Surface Requirements: The surface must be clean, dry and free of dust and grease.
Preliminary Surface Treatment: Make sure that the surface is clean, dry, and free of dust and grease. Remove any sharp and/or protruding parts.